



# Duet Short

## Indoor Lighting - Recessed



Order Code	W	Light Source	Lm	CCT	WxLxH (mm)	Kg
02128.66.30.029	50	LED Module	3970	3000	595x595x90	5.5
02128.66.40.030	50	LED Module	4180	4000	595x595x90	5.5

### TECHNICAL INFORMATION

<b>Housing</b>	Sheet steel housing & aluminium spot lights
<b>Optics</b>	UV-stabilized opal diffuser for panel
<b>Reflector</b>	Dark reflector for spotlights
<b>LED Lifetime</b>	50.000 hours
<b>Mounting System</b>	Recessed

### OPTICAL SPECIFICATIONS

<b>Optical</b>	Symmetrical
<b>Light Exit Angle</b>	48°
<b>UGR Value</b>	80

### ELECTRICAL

<b>Power (W)</b>	50W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz

### OPTIONAL

DALI
Emergency Lighting Unit

### MOUNTING

<b>Mounting Type</b>	Recessed
----------------------	----------



All electrical values given are nominal values. The luminous flux and the associated electrical load are subject to an initial tolerance of +/- 10%. Color temperature tolerance: +/-150 K. Unless otherwise stated, values are valid for an ambient temperature of 25°C. The information containing technical parameters and product codes in the catalog and on the website may differ from standard products due to customizations made according to projects. Ikizler Aydınlatma has the right to make changes to the products without notice. You can get up-to-date information about the products on our website.

**Phone:** +90 (216) 397 22 16  
**Fax:** +90 (216) 397 19 19  
**E-Mail:** info@ikizleraydinlatma.com

Please visit our website for our updated information. [www.ikizleraydinlatma.com](http://www.ikizleraydinlatma.com)

