

Running Trunking System

Indoor Lighting - Linear



TECHNICAL INFORMATION

Housing Extruded aluminum profile with electrostatic coating

OPTICAL SPECIFICATIONS

ELECTRICAL

OPTIONAL

DALI
Emergency Lighting Unit

MOUNTING

Mounting Type Surface, Pendant



* Gövde Sistemi (Kapaksız)



Order Code			WxLxH (mm)	Kg
72530.05.100	5 Wire	On/Off	62x1436x59	1,8
72730.05.100	7 Wire	DALI	62x1436x59	1,9
72930.05.100	9 Wire	DALI + Emergency Kit	62x1436x59	2,0
72530.05.200	5 Wire	On/Off	62x2872x59	3,6
72730.05.200	7 Wire	DALI	62x2872x59	3,8
72930.05.200	9 Wire	DALI + Emergency Kit	62x2872x59	4,0
72530.05.300	5 Wire	On/Off	62x4308x59	5,4
72730.05.300	7 Wire	DALI	62x4308x59	5,7
72930.05.300	9 Wire	DALI + Emergency Kit	62x4308x59	6,0

All electrical values given are nominal values. The luminous flux and the associated electrical load are subject to an initial tolerance of +/- 10%. Color temperature tolerance: +/-150 K. Unless otherwise stated, values are valid for an ambient temperature of 25°C.

The information containing technical parameters and product codes in the catalog and on the website may differ from standard products due to customizations made according to projects.

Ikizler Aydınlatma has the right to make changes to the products without notice. You can get up-to-date information about the products on our website.

Phone: +90 (216) 397 22 16
Fax: +90 (216) 397 19 19
E-Mail: info@ikizleraydinlatma.com

Please visit our website for our updated information. www.ikizleraydinlatma.com

ikizler