

MODUS-T



Standard Colours



Ral 9016

Ral 9006

Ral 9005



OPTICAL

Direct symmetrical distribution

Beam angle 36°

UGR<22

Luminous efficacy >100 lm/W

Lifetime (L90/B10): 50000 h. (tq+25°C)

Lifetime (L80/B20): 100000 h. (tq+25°C)

COB LED module

Color rendering index: CRI>80

MacAdams SDCM 3

MECHANICAL

Extruded aluminium profile housing

Electrostatic powder painted

Aluminium reflector

IP40 protection degree

Impact resistance IK02

Glow-wire test resistance 650°C

ELECTRICAL

Halogen-free wiring

220-240V-50/60Hz

Power factor >0.95

Constant current, Class I,

Driver inside the housing

CE - IEC 60598-1 - EN 60598-1

Ambient temperature from -20°C to +50°C

On-Off Control - (Code: .N000)

OPTIONAL



Color rendering index: CRI >90

Color temperature (K) options

RAL colour selection

INSTALLATION

Ceiling surface mounted.



Product Code	Power (W)	Lumen (lm)	CCT (K)	CRI	Dimensions QxH (mm)	Cut-Out WxL (mm)	Weight (kg)
05648.97.40.014	14	1640	4000K	Ra>80	97x200	N/A	0,9

All electrical values given are rated values. Luminous flux and connected electrical load are subject to an initial tolerance of +/- 10%. Tolerance of colour temperature: +/-150 K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Any information including technical parameters and product codes may differ from standard products in catalogue & web site due to customization made per projects.

Ikizler Lighting has the right to make changes or cancellations on the products without notification. Updated information on the products can be received from our web site.